



DK SERIES

DK751DR5

75" 4000 nits 4K UHD Dual-Sided Ultra-High Brightness Outdoor Kiosk




LOW POWER
CONSUMPTION



SUNLIGHT
VIEWABLE IMAGE



VANDAL
RESISTANT



VIEWABLE WITH
POLARIZED LENSES



WEATHER
PROOF

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan

SPECIFICATION

MODEL	DK751DR5	
DISPLAY	LCD Panel Size	74.52" x2
	Native Resolution	3840 x 2160
	Brightness	4,000 nits
	Color Depth	10 bits
	Contrast Ratio	3000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
Polarized Sunglasses Support	Yes	
POWER	Power Supply	Internal
	Rated Voltage	200-240V ~ 50/60HZ
	Power Consumption (Typ./ Max.)	930 W / 2400 W
MECHANICAL SPECS	Bezel Width (T/B/L/R)	117.6 / 117.6 / 203.5 / 203.5 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	1338.0 x 1962.0 x 254.0 mm
	Monitor Weight	< 442 kg [TBD]
USER INTERFACE	Orientation	Portrait
	Language	English
	Local Dimming Control	Yes
	Support SNMP (Up to V3.0)	Yes
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
INPUT	HDMI 2.1 (HDCP 2.3)	x6 (2160p)
	DisplayPort	x2
	USB 3.0	x2
	Micro SD Slot	x2
OUTPUT	Audio	x2
	RS-232	In x2
EXTERNAL CONTROL	RJ-45	x4 (LAN)
	Operating Temperature	-30°~50° C
ENVIRONMENT	Storage Temperature	-20°~60° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust resistant design	IP56
	Operating System	Android 8.0.0
INTERNAL PLAYER	Processor	Dual-core A73 and dual-core A53
	Clock Speed	1.5GHz
	Main Memory Interface	DDR4, 2G
	Graphics	Quad-core MaliG51
	Storage	Internal: 16GB eMMC Flash External: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32)
	Multimedia	4K 10bits VP9/H265/H264 video decoders, up to 60fps 1080P other video decoders (VC-1, MPEG-1/2/4, VP8)

CERTIFICATION CE / FCC / IEC60950-22 / RoHS

DIMENSIONS

Unit: mm [inch]

